SOLRAD 7A

MACHINE RED. 3 POINTS PER PASS 64-001D-01A

This data set has been restored. There was originally one 7-track, 556 BPI tape written in BCD. There is one restored tape written in ASCII. The DR tape is a 3480 cartridge and the DS tape is 9-track, 6250 BPI. The original tape was created on a 7094 computer. The DR and DS numbers along with the corresponding D number are as follows:

DR#	DS#	D# 	FILES	TIME SPAN
DR004230	DS004230	D002846	1	01/12/64 - 08/31/64

SOLRAD 7A

HAND RED. 1 POINT PER PASS

64-001D-01B

This data set has been restored. There was originally one 7-track, 556 BPI tape written in BCD. There is one restored tape written in ASCII. The DR tape is a 3480 cartridge and the DS tape is 9-track, 6250 BPI. The original tape was created on a 7094 computer. The DR and DS numbers along with the corresponding D number are as follows:

DR#	DS#	D#	FILES	TIME SPAN
DR004231	DS004231	D002847	1	01/11/64 - 02/03/65

OFFIGIAL FILE COPY-MSSDG

64-001D-01A

1964 001D GREB 5 (01) Solar X-Ray

Tapes
D00088
D00089

NAME

DATE

X-RAY AND ULTRA-VIOLET EXPERIMENT

1964 01 D

Machine-reduced Data on 1 Card Image Magnetic Tape - Ot A (3 points per pass)

COLUMN	EXPLANATION
1-2	Year - 1900, i.e., 64
3-4	Month
5-6	Day of month
10-13	Universal time of start of pass Hour - minute
17-20	Universal time of end of pass Hour - minute
25-27	Orbit number
31-32	Station code (see attached list)
38-42 (F5.2)	Aspect angle
45-54 (E9.4)	44-60A flux
57-66 (E9.4)	8-12A flux

Timespan

Jan 12, 1964 to Aug. 31, 1964

The first card is a header card and the second card is blank.

TABLE 2

STATION IDENTIFICATION

CODE	STATION
HV	Hybla Valley, Virginia
SP	South Point, Hawaii
PM	Point Mugu, California
BP	Blossom Point, Md.
MO	Mojave
FM	Fort Myers, Florida
WK	Winkfield, England
CO	College, Alaska
LI	Lima, Peru
QU	Quito, Ecuador
PA	Point Arguello, California
WO	Woomera, Australia
GF	Grand Forks, Michigan
ST	Santiago, Chile
RO	Rosman, North Carolina
UL	Ulaska, Alaska
OR	Ororal
JO	Johannesburg, Union of S. Africa
KO	Kano
KI	Kauai
MA	Madagascar
NE	Newsoundland
CA	Camberria
KP	Kaena Point, Hawaii

STANCE OF STREET

MIFTER	acon
J. o'. vating. Virgibia	711
New Harry and	
stredited as X a	1.79
. W. jerios vaceroji	TE
is validate	• • • • • • OIA
militar (17), second i socie	D'M
in son a breakering	
	(37)
07. °	1.3
ty valence of the period of th	
e committat , ill. tati jete	
6 State / . Whatever	077
ingeleineld je das V derocki	743
elimin, a collowa	
Rogarca, N. sya O welling	40 P
Ulaska, Alasin	. 707
iowell?	
Johanneyburg, Urlan of S. Airlon	
oroX	
inus2i	
Violetases.	AM.
Lanconkoliwe	
ni rinkkisti	
Lacis Point, Liswell	42.

NSSDC ACQUISITION FILE

DATE RECEIVED 10/21/68 MITIALS RPS

ID NUMBER 4264 DOID 01A

FOLDER DSD FILM NUMBER 4

64-0010-01B

X-RAY AND ULTRA-VIOLET EXPERIMENT

1964 01 D

D-00089 C-2847

5046 Pecarta

Hand-reduced Data on 1 Card Image Magnetic Tape (1 point per pass)

Several eards (1 to 5) are present for each station pass reduced. The first 8 columns on each eard are a serial number of unknown function and origin. Similarly an edit card number sometime appears in columns 77-80 of the first eard of a station pass group and probably can be ignored. The first eard of each group contains:

10-11 Year - 1900; i.e., 64 7 2 Month 14-15 Day of month	
in the state of th	
77.22	
Universal time of start of pass () Hour - minute - second	
24-25 Station code (see attached list)	
Pass number	
31-32 Two letters - unknown purpose 8 x	
34-39 Universal time of end of pass Hour - minute - second	
41-50 2 words — unknown purpose	
52-55 & 57-64 Refer to Ultra-violet detectors Purpose unknown	
Refer to pulse width system (sun aspect sensor Purpose unknown	s)
77-80 Edit card number mentioned above	
	, .
Second card: COLUMN EXPLANATION	
17-28 = ASPECT ANGLE	
29-34 (dec. $pt.$ in 32) Aspect angle in degrees $f6.2$ 49-51 = UVI	
53-59 (dec. pt. in 55) Ultra-violet current	

Any or all of the following cards are present to complete the group of cards representing each

st con pass:

EXPLANATION

9-12 = X60 II

13-22 (dec. pt. in 16, E No.) Current in the 44-60A detector

28-31 = X60 F

```
EXPLANATION
   COLUMN
                              Flux for 44-60 A as computed from the 44-60A current
 33-38 (dec. pt. in 34)
                              X020 (X60)F
 44 - 53
                              Flux for 0-20 A as computed from the 44-60A current
  55-60 (dec. pt. in 56)
 63-67
                              X020F
                              Flux for 0-20A computed by adding the 0-8A flux
 69-74 (dec. pt. in 70)
                                from the 2-8 A detector current to the 8-20A
                                flux calculated from the 8-14A detector current
   COLUMN
                             EXPLANATION
  9 - 12
                              X55I
 13-22 (dec. pt. in 16, E No.) Current in the 44-55A detector
 24 - 27
                              X55F
                              Flux for 44-55A as computed from the 44-55A current
 29-35 (dec. pt. in 31)
 38-41
                              X16I
 43-51 (dec. pt. in 45, E No.) Current in the 8-16A detector
                              X820E
 54-58
                              Flux for 8-20A as computed from the 8-16A current
60-66 (dec. pt. in 62)
                              X550F
 68-72
                              Flux for 44-55A as computed from the 44-60A flux
 74-80 (dec. pt. in 76)
                              EXPLANATION
  COLUMN
  9-12
                              X28I
 13-22 (dec. pt. in 16, E No.) Current in the 2-8A detector
 23
                             X Purpose unknown
                         _
 25-28
                              X08F
                              Flux for 0-8A as computed from the 2-8A current
 30-36 (dec. pt. in 32)
 39-42
                              X14I
 44-52 (dec. pt. in 46, E No.) Current in the 8-14A detector
                              X12F
 55-58
                              Flux for 8-12A as computed from 8-14A detector 1
 60-66 (dec. pt. in 62)
 68 - 72
                              X820F
                              Flux for 8-20A as computed from the 8-14A detector
 74-80 (dec. pt. in 76)
```

Timespan of Data

Ultra-violet detectors

44-55A detector

8-16A detector

2-8A detector

8-14A detector

44-60A detector

Jan 11, 1964 to Jan. 12, 1964

Jan 11, 1964 to Feb. 6, 1964

Jan 11, 1964 to Feb. 6, 1964

Jan 11, 1964 to Feb. 3, 1965

×16

TABLE 2

STATION IDENTIFICATION

CODE	STATION
HV	Hybla Valley, Virginia
SP	South Point, Hawaii
Р́М	Point Mugu, California
BP	Blossom Point, Md.
MO	Mojave
FM .	Fort Myers, Florida
WK	Winkfield, England
_Q0	College, Alaska
LI	Lima, Peru
QU	Quito, Ecuador
PA	Point Arguello, California
WO	Woomera, Australia
GF	Grand Forks, Michigan
ST	Santiago, Chile
RO	Rosman, North Carolina
UL	Ulaska, Alaska
OR	Offoral
JO	-Johannesburg, Union of S. Africa
KO	Kano
KI	Kauai
MA	Madagascar
NE	Newfoundland
CA	Cahberria
KP	Kaena Point, Hawaii

OFFICE FILE COPY-165500

X-RAY AND ULTRA-VIOLET EXPERIMENT

1964 01 D

Hand-reduced Data on 1 Card Image Magnetic Tape - O(B)
(1 point per pass)

Several cards (1 to 5) are present for each station pass reduced. The first 8 columns on each card are a serial number of unknown function and origin. Similarly an edit card number sometime appears in columns 77-80 of the first card of a station pass group and probably can be ignored. The first card of each group contains:

	COLUMN	EXPLANATION
	10-11	Year - 1900, i.e., 64
	12-13	Month
	14-15	Day of month
1.	17-22	Universal time of start of pass
		Hour - minute - second
	24-25	Station code (see attached list)
	26-29	Pass number
	31-32	Two letters - unknown purpose
	34-39	Universal time of end of pass
	41 50	Hour - minute - second
	41-50	2 words — unknown purpose
	52-55 & 57-64	Refer to Ultra-violet detectors Purpose unknown
	65-70	Refer to pulse width system (sun aspect sensors) Purpose unknown
	77-80	Edit card number mentioned above
Second card:	COLUMN	EXPLANATION
	17-28 =	ASPECT ANGLE
	29-34 (dec. pt. in 32)	Aspect angle in degrees
	49-51 =	UVI
	53-59 (dec. pt. in 55)	Ultra-violet current

Any or all of the following cards are present to complete the group of cards representing each station pass:

9-12 = X60 I 13-22 (dec. pt. in 16, E No.) Current in the 44-60A detector 28-31 = X60F

```
EXPLANATION
 COLUMN
                             Flux for 44-60 A as computed from the 44-60A current
33-38 (dec. pt. in 34)
                             X020 (X60)F
44 - 53
                             Flux for 0-20 A as computed from the 44-60A current
55-60 (dec. pt. in 56)
                             X020F
63-67
                             Flux for 0-20A computed by adding the 0-8A flux
69-74 (dec. pt. in 70)
                               from the 2-8 A detector current to the 8-20A
                               flux calculated from the 8-14A detector current
                           EXPLANATION
 COLUMN
                             X55I
 9 - 12
13-22 (dec. pt. in 16, E No.) Current in the 44-55A detector
                             X55F
24 - 27
                             Flux for 44-55A as computed from the 44-55A current
29-35 (dec. pt. in 31)
                             X16I
38 - 41
43-51 (dec. pt. in 45,E No.) Current in the 8-16A detector
                             X820F
54 - 58
                             Flux for 8-20A as computed from the 8-16A current
60-66 (dec. pt. in 62)
                             X550F
68 - 72
                             Flux for 44-55A as computed from the 44-60A flux
74-80 (dec. pt. in 76)
                             EXPLANATION
 COLUMN
                             X28I
 9 - 12
13-22 (dec. pt. in 16, E No.) Current in the 2-8A detector
                             X Purpose unknown
23
                        =
                             X08F
25-28
                             Flux for 0-8A as computed from the 2-8A current
30-36 (dec. pt. in 32)
                             X14I
39 - 42
44-52 (dec. pt. in 46, E No.) Current in the 8-14A detector
                             X12F
                        =
55-58
                             Flux for 8-12A as computed from 8-14A detector
60-66 (dec. pt. in 62)
                        =
                             X820F
68 - 72
                             Flux for 8-20A as computed from the 8-14A detector
74-80 (dec. pt. in 76)
```

Timespan of Data

Ultra-violet detectors 44-55A detector 8-16A detector	Jan 11, 1964 to Jan. 12, 1964 Jan 11, 1964 to Feb. 6, 1964 Jan 11, 1964 to Feb. 6, 1964
2-8A detector 8-14A detector 44-60A detector	Jan 11, 1964 to Feb. 3, 1965

File 1 RECORD 1 84 BYTES

DATE START STOP ORBIT ST ASP.ANG. 44-60 FLUX 8-12 FLUX

ASCII LIST OF DS004230

FILE 1 RECORD 2 84 BYTES

ASCII LIST OF DS004230

LE 1 RECORD 3 84 BYTES

64 112 1438 1454 11 CO 0.00 .0000E-99 .0000E-99

ASCII LIST OF DS004230

FILE 1 RECORD 4 84 BYTES

64 112 1958 2013 14 CO 0.00 .0000E-99 .0000E-99

ASCII LIST OF DS004230

FILE 1 RECORD 5 84 BYTES

113 1651 1706 26 FM 0.00 .0000E-99 .0000E-99

File 1 RECORD 3211 84 BYTES

64 831 1954 1955 3242 ST 0.00 .0000E-99 .0000E-99

ASCII LIST OF DS004230

FILE 1 RECORD 3212 84 BYTES

64 831 2053 2108 3243 CO 18.45 .1999E-01 .0000E-99

ASCII LIST OF DS004230

LE 1 RECORD 3213 84 BYTES

64 831 2104 2118 3243 MU 0.00 .0000E-99 .0000E-99

ASCII LIST OF DS004230

FILE 1 RECORD 3214 84 BYTES

64 831 2105 2116 3243 MO 0.00 .0000E-99 .0000E-99

ASCII LIST OF DS004230

FILE 1 RECORD 3215 84 BYTES

831 2240 2251 3244 CO 0.00 .0000E-99 .0000E-99

File 1 RECORD 1 84 BYTES

01112146 640111 214620 SP0001 CT 220140 5X60 6 UVO 7X14X16 8PW 253B

ASCII LIST OF DS004231

FILE 1 RECORD 2 84 BYTES

1112146 ASPECT ANGLE .98 UVI .2276

ASCII LIST OF DS004231

LE 1 RECORD 3 84 BYTES

1112146X60I -1.7623 3 X60F .0177 X020%X60<F .0417 X020F .0098

ASCII LIST OF DS004231

FILE 1 RECORD 4 84 BYTES

1112146X55I .9744 3 X55F .0114 X16I -.3399 3 X820F .0066 X550F .0122

ASCII LIST OF DS004231

FILE 1 RECORD 5 84 BYTES

12146X28I 0.0000 4X X08F 0.0000 X14I .2199 3 X12F .0026 X820F .0098

File 1 RECORD 5041 84 BYTES

2 32048 X

ASCII LIST OF DS004231

FILE 1 RECORD 5042 84 BYTES

2 32227 65 2 3 222730 HV5415 BT 224230 5X60 6 0 7 X14 8PW XSAT847B

ASCII LIST OF DS004231

LE 1 RECORD 5043 84 BYTES

2 32227 ASPECT ANGLE 14.80 PW

ASCII LIST OF DS004231

FILE 1 RECORD 5044 84 BYTES

2 32227X60I -3.1021 9 X60F .0313 X020%X60<F .0735 X020F 0.0000

ASCII LIST OF DS004231

FILE 1 RECORD 5045 84 BYTES

32227 X